

		Copeland Packed Unit (Vertical Discharge)						
Model		MCSG08/U	MCSG10/U	MCSG13/U	MCSG15/U	MCSG20/V	MCSG25/V	MCSG30/V
Room Temperature (°C)		-15℃ ~ +5℃						
Refrigerant		R404A / R448A / R449A						
Power Supply		380V/3P/50HZ						
Compressor		ZB58KQE	ZB76KQE	ZB95KQE	ZB114KQE	ZB130KQE	ZB190KQE	ZB220KQE
Condenser Fan	Fan Qty	Φ550 	Φ500  	Φ500  	Φ550  	Φ550  	Φ630  	Φ700  
	Input (W)	600	2 X 380	2 X 380	2 X 600	2 X 600	2 X 800	2 X 750
	Fan Voltage	380V/3P/50HZ 6poles						
Condenser	Heat Exchange Area (m²)	70	90	110	120	155	210	240
	Heat Exchange Capacity (W)	24640	30500	39050	42240	55025	72660	82800
Evap -5℃	Cooling Capacity (W)	15224	20306	24843	29593	39264	50300	62090
	Lnput (kw)	6.41	8.35	10.77	12.75	15.63	20.63	24.85
Evap -10℃	Cooling Capacity (W)	12588	14511	20591	24344	32737	42000	51880
	Lnput (kw)	6.38	8.28	10.71	12.73	15.49	20.45	24.64
Evap -15℃	Cooling Capacity (W)	10213	13846	16673	19618	26932	34900	43070
	Lnput (kw)	6.38	8.22	10.69	12.73	15.28	20.25	24.4
Evap -20℃	Cooling Capacity (W)	8004	11163	14060	16768	21698	28780	35540
	Lnput (kw)	6.42	8.17	10.5	12.71	15	19.95	24.04
Pipe	Gas (inch)	7/8	7/8	7/8	1	1-1/8	1-1/4	1-1/4
	Liquid (inch)	5/8	5/8	5/8	3/4	3/4	7/8	7/8
Dimension (mm)		900x770x1000	1330x950x890	1480x950x990	1730x1050x1000	1600x1000x1650	1750x1000x1880	1900x1175x1980

Remarks: Condensing temp:45°C

		Danfoss Packed Unit (Horizontal Discharge)					
Model		MCSD-02Z	MCSD-03Z	MCSD-04Z	MCSD-05Z	MCSD-06Z	MCSD-07Z
Room Temperature (°C)		-18°C ~ +5°C					
Refrigerant		R404A / R448A / R449A					
Power Supply		380V/3P/50HZ					
Compressor		MLZ015T4	MLZ021T4	MLZ030T4	MLZ038T4	MLZ045T4	MLZ048T4
Condenser Fan	Fan Qty	Φ450 	Φ450 	Φ450 	Φ400  	Φ400  	Φ400  
	Air Flow(m3/h)	4500	4500	4500	4500	7490	7490
	Fan Voltage	220V/1P/50HZ 4poles					
Evap 0°C	Cooling Capacity (W)	4560	6231	9439	11495	13386	14899
	Input (kw)	1.95	2.5	3.6	4.3	5.1	5.57
Evap -10°C	Cooling Capacity (W)	3130	4324	6556	7943	9541	10323
	Input (kw)	1.85	2.48	3.5	4.21	5.02	5.48
Evap -15°C	Cooling Capacity (W)	2538	3705	5382	6394	7932	8601
	Input (kw)	1.82	2.45	3.45	4.18	4.95	5.42
Evap -20°C	Cooling Capacity (W)	1995	3040	4512	5367	6370	6975
	Input (kw)	1.8	2.42	3.4	4.15	4.9	5.35
Evap -25°C	Cooling Capacity (W)	1581	2500	3657	4230	5320	5605
	Input (kw)	1.75	2.4	3.37	4.1	4.87	5.3
Pipe	Gas (inch)	3/4	3/4	7/8	7/8	7/8	7/8
	Liquid (inch)	3/8	1/2	1/2	1/2	1/2	1/2
Dimension (mm)		1100x475x610	1100x475x610	1100x475x1130	1100x475x1130	1100x475x1130	1100x475x1130

Remarks: Condensing temp:45°C



Copeland® Scroll Compressor Unit with Electrical Control



Product Description:

- Traditional CU/AL Condenser;
- Low Noise/High Efficient Axial Fan Motor;
- Original Danfoss/Copeland/Highly Refrigeration Components;
- Extraordinary Cost-Effectiveness Performance.
- Electrical control inside.



Nomenclature:

M¹ **CS**² **D**³ - **02**⁴ **Z**⁵

- 1 Temperature M:** -5 ~ +5°C, **L:** -20 ~ -15°C
- 2 CU/AL Condenser with Horizontal Air Discharge housing**
- 3 Compressor Type D:** Danfoss, **G:** Copeland
- 4 HP**
- 5 Refrigerant Z:** for R404A / R448A / R449A

Copeland Packed Unit (Horizontal Discharge)

Model	MCSG-02Z	MCSG-03Z	MCSG-04Z	MCSG-05Z	MCSG-06Z	MCSG-07Z
Room Temperature (°C)	-15°C ~ +5°C					
Refrigerant	R404A / R448A / R449A					
Power Supply	380V/3P/50HZ					
Compressor	ZB15KQE	ZB21KQE	ZB29KQE	ZB38KQE	ZB45KQE	ZB48KQE
Condenser Fan	Fan Qty Φ450	Fan Qty Φ450	Fan Qty Φ400	Fan Qty Φ400	Fan Qty Φ400	Fan Qty Φ400
Condenser	220V/1P/50HZ 6poles					
	Heat Exchange Area (m²)	21	30.3	37.2	45.5	54
	Condensing Capacity (kw)	5.6	8	9.9	12.1	14.4
Evap -5°C	Fin Space (mm)	2	2	2	2	2
	Cooling Capacity (W)	3820	5740	7840	9720	11450
Evap -10°C	Lnput (kw)	1.76	2.5	3.32	4.2	4.79
	Cooling Capacity (W)	3070	4680	6370	7910	9310
Evap -15°C	Lnput (kw)	1.82	2.51	3.35	4.2	4.81
	Cooling Capacity (w)	2430	3780	5120	6380	7510
Evap -20°C	Lnput (kw)	1.88	2.52	3.37	4.2	4.82
	Cooling Capacity (W)	1860	3010	4070	5090	6000
Pipe	Lnput (kw)	1.93	2.52	3.39	4.19	4.81
	Gas (inch)	3/4	3/4	7/8	7/8	7/8
Dimension (mm)	Liquid (inch)	3/8	1/2	1/2	1/2	1/2
		1300x560x690	1300x560x690	1300x560x990	1300x560x990	1300x560x990

Condensing temp:45°C

Copeland Packed Unit (Horizontal Discharge)

Model	LCSG-02Z	LCSG-03Z	LCSG-04Z	LCSG-05Z	LCSG-06Z	LCSG-07Z
Room Temperature (°C)	-25°C ~ -10°C					
Refrigerant	R404A / R448A / R449A					
Power Supply	380V/3P/50HZ					
Compressor	ZSI06KQE	ZSI09KQE	ZSI11KQE	ZSI15KQE	ZSI18KQE	ZSI21KQE
Condenser Fan	Fan Qty Φ450	Fan Qty Φ450	Fan Qty Φ400	Fan Qty Φ400	Fan Qty Φ400	Fan Qty Φ400
Condenser	220V/1P/50HZ 6poles					
	Heat Exchange Area (m²)	21	30.3	37.2	45.5	54
	Condensing Capacity (kw)	5.6	8	9.9	12.1	14.4
Evap -20°C	Fin Space (mm)	2	2	2	2	2
	Cooling Capacity (W)	2330	3240	4120	5930	7230
Evap -25°C	Lnput (kw)	1.79	2.25	2.63	3.59	4.44
	Cooling Capacity (W)	1880	2620	3340	4830	5910
Evap -30°C	Lnput (kw)	1.73	2.2	2.57	3.44	4.28
	Cooling Capacity (W)	1500	2070	2610	3790	4780
Pipe	Lnput (kw)	1.66	2.12	2.44	3.3	4.17
	Gas (inch)	3/4	3/4	7/8	7/8	7/8
Dimension (mm)	Liquid (inch)	3/8	1/2	1/2	1/2	1/2
		1300x560x690	1300x560x690	1300x560x990	1300x560x990	1300x560x990

Remarks: Condensing temp:45°C